

PREMIUM GRADE

PAINT MASKING TAPE

CF 30

Introducing CF 30, the premier masking tape for detail painting projects.

Its fine structured crepe backing allows you to easily round corners and edge any irregular shape. When painting molding and trim, CF 30 is the perfect solution. Apply it to painted sheet rock, wood, wallboard, or ceramic tile and it removes cleanly every time. CF 30's backing also reduces bleed-through to prevent costly clean up.

CF 30 is a natural colored painter's tape that provides easy unwind with excellent conformability. It works especially well with spray primers and knock-downs for walls. It offers superior paint lines while resisting abrasion, moisture, and curling.



Shurtape®

www.shurtape.com 1.888.422.TAPE

PREMIUM GRADE

PAINT MASKING TAPE



When painting molding and trim, CF 30 is the perfect solution. Apply it to painted sheet rock, wood, wallboard, or ceramic tile and it removes cleanly every time.



A fine structured crepe backing makes CF 30 excellent for rounding curves and contours.

CF 30



Premium Grade

Masking Tape for:

- painting trim and molding
- masking wallboard, woodwork, ceramic tile, and painted sheet rock

- Fine structured crepe backing rounds curves and contours
- Easy release off the roll
- Good quick stick
- Clean removal

Tensile	23 lbs/in width
Adhesion to Stainless Steel	34 oz/in width
Thickness	7.1 mils
Elongation	10%
Service Temperature Range	45°-100° F

CP 66



Contractor Grade

Painter's Tape for:

- painting and construction
- masking wood trim, carpet and vinyl flooring

- Easy release off the roll
- Flexible
- Good quick stick
- Conforms well to irregular surfaces

Tensile	21 lbs/in width
Adhesion to Stainless Steel	39 oz/in width
Thickness	5.9 mils
Elongation	8%
Service Temperature Range	50°-150° F

Colonial



Premium Grade

Painter's Tape for:

- masking rough surfaces, wood trim, and flooring

- Easy unwind
- Good quick stick
- Resists water, oils and solvents

Tensile	22 lbs/in width
Adhesion to Stainless Steel	39 oz/in width
Thickness	6.7 mils
Elongation	10%
Service Temperature Range	50°-150° F

CP 20



SHURelease®

Multiple Surface

Painter's Tape for:

- masking painted surfaces, wood, and metal
- securing drop cloths

- 8-day UV resistant
- Removes cleanly
- Resists paint bleed-through

Tensile	22 lbs/in width
Adhesion to Stainless Steel	33 oz/in width
Thickness	6.1 mils
Elongation	8%
Service Temperature Range	50°-150° F

CP 27



SHURelease®

Multiple Surface

Painter's Tape for:

- masking glass, painted surfaces, wood, and metal

- 14-day UV resistant
- Removes cleanly

Tensile	24 lbs/in width
Adhesion to Stainless Steel	21 oz/in width
Thickness	5.7 mils
Elongation	6%

CP 28



SHURelease®

Delicate Surface

Painter's Tape for:

- masking drywall, wallpaper, and freshly painted surfaces

- 30-day UV resistant
- Removes cleanly
- Low tack, high performance

Tensile	25 lbs/in width
Adhesion to Stainless Steel	8 oz/in width
Thickness	5.1 mils
Elongation	5%

ISO 9000 CERTIFIED QUALITY SYSTEM

© 2009 Shurtape Technologies, LLC

"Shurtape" is a registered trademark of Shurtape Technologies, LLC.

♻️ Printed in USA on recycled paper.

Form #SS-CF030-07/13/09

Shurtape®

www.shurtape.com 1.888.422.TAPE