

PREMIUM GRADE

DOUBLE-SIDED CLOTH TAPE

DF 545

Engineered with a versatile adhesive system for strength and clean removal.

DF 545 is primarily used for carpet installation as well as industrial holding, mounting and splicing. Convention centers routinely recommend our low-residue double sided tapes for trade shows. We created DF 545 with the same clean removal adhesive system and beefed up its tensile strength.

When mold abatement or asbestos remediation calls for a moisture-free, airtight seal, Shurtape DF 545 is the perfect solution. It adheres to irregular surfaces, seals solidly and removes cleanly.

- > Blended natural and synthetic rubber provides superior adhesion to concrete, tile, hardwood flooring and other irregular surfaces.
- > Special poly laminate and high tensile cloth promotes clean removability.
- > Premium grade, silicone coated blue polyethylene release liner ensures easy removability from the adhesive backing.
- > Strength, flexibility and clean removal – setting the standard for demanding construction, convention and abatement applications.



Shurtape®

www.shurtape.com 1.888.442.TAPE

PREMIUM GRADE

DOUBLE-SIDED CLOTH TAPE



DF 545



Multi-Purpose Double-Sided Cloth Tape for holding down carpet, hanging poly sheeting, and splicing applications.

- Natural/synthetic blend adhesive
- Residue-free removal
- Easy unwind
- Airtight seal

Tensile Strength	25 lbs/in width
Adhesion to Stainless Steel	45 oz/in width
Thickness	15.5 mils
Elongation	9%
Service Temperature Range	Up to 200° F



DF 642



Multi-Purpose Double-Sided Cloth Tape for holding down carpet, hanging poly sheeting, signs and dispensers for POP merchandising.

- Industrial grade, aggressive rubber adhesive
- Residue-free removal
- Easy unwind
- Airtight seal

Tensile Strength	32 lbs/in width
Adhesion to Stainless Steel	29 oz/in width
Thickness	12.0 mils
Elongation	8%
Service Temperature Range	Up to 225° F

PC 600



General Purpose Duct Tape for packaging, sealing, holding carpet pad, color coding, seaming and bundling.

- Waterproof backing
- Conformable
- Easy to tear
- Easy to unwind
- Strong natural rubber adhesive

Tensile Strength	22 lbs/in width
Adhesion to Stainless Steel	50 oz/in width
Thickness	9.0 mils
Elongation	10%
Service Temperature Range	Up to 200° F

REGIONAL SALES OFFICES & DISTRIBUTION CENTERS

North Carolina

Catawba Industrial Place
3389 Catawba Industrial Place
Catawba, NC 28609

tel: (828) 322-2700
(888) 442-8273
fax: (828) 322-4029

Arizona

First Commerce Center
725 N 73rd Avenue, Suite 112
Phoenix, AZ 85043

tel: (623) 463-5886
(800) 342-8273
fax: (623) 463-5809

ISO 9000 CERTIFIED QUALITY SYSTEM

© 2009 Shurtape Technologies, LLC

"Shurtape" is a registered trademark of Shurtape Technologies, LLC.

♻️ Printed in USA on recycled paper.

Form #SS-PC610-06/23/2009-P500

Shurtape®

www.shurtape.com 1.888.442.TAPE