

TEMPERATURE-RESISTANT

HIGH PERFORMANCE MASKING TAPES

HIGH PERFORMANCE

Engineered for the transportation industry, our residue-free tapes hold up under extreme conditions.

Our premium masking tapes offer heat resistance and clean removal in any temperature range. Ideal for use in painting, metal fabrication and powder coating in the transportation and marine industries, our high performance masking tapes can resist a range of temperatures, up to 350° F. Even when subject to high temperatures, a cured rubber adhesive system allows clean removal from metal, rubber, plastics and other surfaces. These tapes won't leave behind adhesive residue, only sharp paint lines.

- > Resists solvents and moisture to minimize paint bleed-through and rework.
- > Compatible with polyurethane paints.
- > Strong crepe paper backing resists tears and slivers.
- > Superior conformability to irregular surfaces.



Shurtape®

www.shurtape.com 1.888.442.TAPE

TEMPERATURE-RESISTANT

HIGH PERFORMANCE MASKING TAPES



CP 400



Performance Masking tape for use in the transportation industry.

- Smooth crepe backing
- Easy handling
- Crisp paint lines
- Clean removal
- Economical

Tensile Strength	20 lbs/in width
Adhesion to Stainless Steel	30 oz/in
Thickness	6.0 mils
Elongation	10 %
Service Temperature Range	Up to 200° F



CP 450



Heavy Duty Performance Masking tape for demanding applications in the transportation industry.

- Heavy duty crepe backing
- Resists paint bleed-through
- Residue-free
- Solvent & moisture resistant
- Ideal for wet sanding

Tensile Strength	28 lbs/in width
Adhesion to Stainless Steel	34 oz/in
Thickness	6.6 mils
Elongation	10 %
Service Temperature Range	Up to 200° F



CP 500



Performance Masking tape for high-temperature painting on cars, buses, and wet sanding applications.

- Smooth crepe backing
- Easy unwind
- Excellent quick stick
- Resists solvents
- Sharp paint lines

Tensile Strength	25 lbs/in width
Adhesion to Stainless Steel	36 oz/in
Thickness	6.4 mils
Elongation	10 %
Service Temperature Range	Up to 300° F

CP 650



Heavy Duty Performance Masking tape for high temperature painting in the transportation industry.

- Strong, smooth heavy duty crepe backing
- Withstands multiple bake cycles
- Removes cleanly
- Solvent & moisture resistant
- Resistant to wet sanding

Tensile Strength	30 lbs/in width
Adhesion to Stainless Steel	34 oz/in
Thickness	6.6 mils
Elongation	10 %
Service Temperature Range	Up to 325° F

CF 740



Very High Temperature Masking tape for applications in the transportation, marine and metal fabrication industries.

- Fine structured crepe backing
- Prevents paint bleed-through
- No residue
- Easy unwind

Tensile Strength	24 lbs/in width
Adhesion to Stainless Steel	31 oz/in
Thickness	6.7 mils
Elongation	10 %
Service Temperature Range	Up to 350° F

ISO 9000 CERTIFIED QUALITY SYSTEM

© 2009 Shurtape Technologies, LLC

"Shurtape" is a registered trademark of Shurtape Technologies, LLC.

♻️ Printed in USA on recycled paper.

Form #SS-HiPerfMask- 06/25/2009-P1M

Shurtape®

www.shurtape.com 1.888.442.TAPE