

UL-LISTED

# HVAC DUCT SEALING TAPES

# HVAC

Meet code on every job. Seal it with Shurtape.

Sealing ductboard, flex duct or sheet metal? Shurtape has a full line of all-weather foil tape, flexible film tape, cloth duct tape, and roll mastics for the HVAC contractor. We work with contractors, building inspectors and code enforcers to ensure our tapes meet UL performance standards.

Use our UL-listed tapes and you'll never worry about meeting code. You'll get the job done right the first time with our consistent quality - roll after roll.

- > Superior shear adhesion holds a 100-gram load without slipping (24 hour evaluation after exposure to 150°F for 60 days)
- > No adverse effects after exposure for 60 days up to 212°F
- > High resistance to mold growth and humidity
- > UL 181 listed specification printed directly on the tape is easily identified by inspectors



**Shurtape®**

[www.shurtape.com](http://www.shurtape.com) 1.888.442.TAPE

UL-LISTED

# HVAC DUCT SEALING TAPES



## AF 100



UL-listed Aluminum Foil Tape for joining and sealing Class 1 Flex Duct, sheet metal, and fiberglass ductboard.

- UL 181A-P/B-FX listed
- Air-tight seal
- Flexible and easy to use
- Excellent adhesion

<b>Tensile Strength</b>	25 lbs/in width
<b>Adhesion to Stainless Steel</b>	75 oz/in width
<b>Thickness</b>	4.2 mils
<b>Elongation</b>	2 %
<b>Service Temperature Range</b>	-20° to 250° F



## DC 181



UL-listed Flexible Film Duct Tape for connecting, joining, sealing, and patching flexible air ductwork.

- UL 181B-FX listed
- Cold weather adhesive
- Available in Black w/White print; Silver Metalized w/Black print; Clear w/Green print

<b>Tensile Strength</b>	22 lbs/in width
<b>Adhesion to Stainless Steel</b>	41 oz/in width
<b>Thickness</b>	3.0 mils
<b>Elongation</b>	50 %
<b>Service Temperature Range</b>	-35° to 210° F



## LS 300



UV-Resistant Line Set Tape for protecting HVAC line sets.

- Durable OPP film and acrylic adhesive
- High adhesion
- Easy to use

<b>Tensile Strength</b>	22 lbs/in width
<b>Adhesion to Stainless Steel</b>	35 oz/in width
<b>Thickness</b>	3.0 mils
<b>Elongation</b>	50 %
<b>Service Temperature Range</b>	-35° to 210° F



## PC 857



UL-listed Duct Tape for joining and sealing Class 1 Flex Duct. Installing air ducts and air connectors.

- UL 181B-FX listed
- Resists flame spread, smoke, and mold growth
- Printed tape available in Black, Gray and Metalized

<b>Tensile Strength</b>	27 lbs/in width
<b>Adhesion to Stainless Steel</b>	60 oz/in width
<b>Thickness</b>	14.0 mils
<b>Elongation</b>	10 %
<b>Service Temperature Range</b>	50° to 200° F

## SF 686



Shurflex Indoor/Outdoor Roll Mastic for sealing rigid and flexible air duct systems. Suitable for subgrade application on PVC coated duct.

- UL 181B-FX listed
- Air-tight and moisture-free seals
- Paintable foil
- Permanent bonds
- No asbestos, CFCs, or PCBs

<b>Adhesion to Stainless Steel</b>	100 oz/in width
<b>Thickness</b>	17.0 mils
<b>Service Temperature Range</b>	-20° to 200° F

ISO 9000 CERTIFIED QUALITY SYSTEM

© 2008 Shurtape Technologies, LLC

"Shurtape" is a registered trademark of Shurtape Technologies, LLC.

♻️ Printed in USA on recycled paper.

Form #SS-ULListed-09/08/2008-P2M

# Shurtape®

www.shurtape.com 1.888.442.TAPE