

UV-RESISTANT

# LINE SET TAPE

LS 300

Did you know there is a special tape made for line sets?

Shurtape's new LS 300 Line Set Tape is a specialty UV resistant tape made just for covering HVAC line sets. LS 300 acts as a protective shield on line sets—protecting them from harsh sunlight that over time degrades unprotected or poorly protected foam insulation.

Unlike conventional electrical tape or duct tape, LS 300 is made of polypropylene film that unwinds easily and conforms to irregular surfaces. And the polypropylene film is built for the outdoors—it stands up to rain, snow, sleet, even temperatures ranging from -35°F to 210° F.

This specialty tape is an essential product for the tool box of HVAC contractors who want to complete their installations with a tidy and long lasting seal.

> **Durable OPP film and acrylic adhesive**

LS 300 will not delaminate over time. The combination of polypropylene film and acrylic adhesive makes LS 300 printed film tape durable and long lasting.

> **High adhesion**

Excellent holding power—even in extreme weather. Adheres quickly and easily to foam pipe insulation and HVAC components.

> **Easy to use**

Conforms easily to the curves and contours of line sets.



**HOLD STRONG.**

[www.shurtape.com](http://www.shurtape.com) 1.888.442.TAPE

UV-RESISTANT

# LINE SET TAPE



## LS 300



UV-Resistant Line Set Tape for protecting HVAC line sets.

- Durable OPP film and acrylic adhesive
- High adhesion
- Easy to use

<b>Tensile Strength</b>	22 lbs/in width
<b>Adhesion to Stainless Steel</b>	35 oz/in width
<b>Thickness</b>	3.0 mils
<b>Elongation</b>	50 %
<b>Service Temperature Range</b>	-35° to 210° F

## Shurtape offers a full line of HVAC products



## DC 181



UL-listed Flexible Film Duct Tape for connecting, joining, sealing, and patching flexible air ductwork.

- UL 181B-FX listed
- Cold weather adhesive
- Available in Black with White print; Silver Metalized with Black print

<b>Tensile Strength</b>	22 lbs/in width
<b>Adhesion to Stainless Steel</b>	41 oz/in width
<b>Thickness</b>	3.0 mils
<b>Elongation</b>	50 %
<b>Service Temperature Range</b>	-35° to 210° F



## AF 100



UL-listed Aluminum Foil Tape for joining and sealing Class 1 Flex Duct, sheet metal, and fiberglass ductboard.

- UL 181A-P/B-FX listed
- Air-tight seal
- Flexible and easy to use
- Excellent adhesion

<b>Tensile Strength</b>	25 lbs/in width
<b>Adhesion to Stainless Steel</b>	75 oz/in width
<b>Thickness</b>	4.2 mils
<b>Elongation</b>	2 %
<b>Service Temperature Range</b>	-20° to 250° F



## PC 857



UL-listed Duct Tape for joining and sealing Class 1 Flex Duct. Installing air ducts and air connectors.

- UL 181B-FX listed
- Resists flame spread, smoke, and mold growth
- Printed tape available in Black, Gray and Metalized

<b>Tensile Strength</b>	27 lbs/in width
<b>Adhesion to Stainless Steel</b>	60 oz/in width
<b>Thickness</b>	14.0 mils
<b>Elongation</b>	10 %
<b>Service Temperature Range</b>	50° to 200° F

## SF 686



Shurflex Indoor/Outdoor Roll Mastic for sealing rigid and flexible air duct systems. Suitable for subgrade application on PVC coated duct.

- UL 181B-FX listed
- Air-tight and moisture-free seals
- Paintable foil
- Permanent bonds
- No asbestos, CFCs, or PCBs

<b>Adhesion to Stainless Steel</b>	200 oz/in width
<b>Thickness</b>	17.0 mils
<b>Service Temperature Range</b>	-20° to 200° F

ISO 9000 CERTIFIED QUALITY SYSTEM

© 2007 Shurtape Technologies, LLC

"Shurtape" is a registered trademark of Shurtape Technologies, LLC.

Printed in USA on recycled paper.

Form #SS-LS300-10/29/2007-P1M

# Shurtape

www.shurtape.com 1.888.442.TAPE