

ECONOMY GRADE

CLOTH DUCT TAPE

PC 590

We call it PC 590. You'll call it the Industry Standard.

Shurtape PC 590 demonstrates superior quality in a 7 mil duct tape. Utilizing our state-of-the-art calendaring process, PC 590 sets the standard for the economy grade market and it rounds out our full line of industrial grade products. PC 590 works in a wide range of applications and provides dependable results every time.

Use PC 590 for packaging, bundling, sealing, seaming, repairing, holding and waterproofing. Its aggressive tack and easy handling make it the right choice for everyday jobs.



Shurtape®

www.shurtape.com 1.888.442.TAPE

ECONOMY GRADE

CLOTH DUCT TAPE



PC 590



Economy Grade

Cloth Duct Tape for:

- packaging, bundling, sealing, repairing, holding, and waterproofing
- plumbing and asbestos abatement

- Aggressive tack
- Good adhesion
- Excellent conformability
- Good handling – does not twist or curl during application

Tensile Strength	20 lbs/in width
Adhesion to Stainless Steel	45 oz/in width
Thickness	7.0 mils
Elongation	15 %
Service Temperature Range	50° to 200° F



Find the tape you need in our full line of duct tapes.

PC 600



General Purpose Cloth Duct

Tape for:

- home and general repairs
- color coding
- sealing, seaming and waterproofing

- 14 colors
- Easy tear
- High tack
- Does not twist or curl during application

Tensile Strength	22 lbs/in width
Adhesion to Stainless Steel	45 oz/in width
Thickness	9.0 mils
Elongation	10 %
Service Temperature Range	50° to 200° F



PC 618



Light Industrial Grade Cloth Duct Tape for:

- color coding
- sealing hatch covers, cargo doors
- repairing & bundling
- book binding

- Wide variety of colors
- Waterproof
- Easy tear and unwind
- Excellent tack and holding power

Tensile Strength	27 lbs/in width
Adhesion to Stainless Steel	50 oz/in width
Thickness	10.0 mils
Elongation	15 %
Service Temperature Range	50° to 200° F



PC 620



Industrial Grade Cloth Duct Tape for:

- general industrial repairs
- sealing HVAC ducts
- bundling, splicing, masking

- Waterproof
- Easy tear and unwind
- Excellent tack, holding power, and conformability

Tensile Strength	27 lbs/in width
Adhesion to Stainless Steel	50 oz/in width
Thickness	11.0 mils
Elongation	10 %
Service Temperature Range	50° to 200° F

PC 622



Premium Grade Cloth Duct Tape for:

- high performance motorsports
- stucco masking
- silk screening
- heavy duty jobs

- Waterproof
- High tensile strength
- Excellent holding power
- Conformable

Tensile Strength	40 lbs/in width
Adhesion to Stainless Steel	55 oz/in width
Thickness	12.5 mils
Elongation	10 %
Service Temperature Range	50° to 200° F

ISO 9000 CERTIFIED QUALITY SYSTEM

© 2009 Shurtape Technologies, LLC

"Shurtape" is a registered trademark of Shurtape Technologies, LLC.

♻️ Printed in USA on recycled paper.

Form #SS-PC590-06/25/2009-P1M

Shurtape®

www.shurtape.com 1.888.442.TAPE